

ALUSPEED DOOR HIGH SPEED ALUMINIUM ROLL UP DOOR

High Speed Door for interior & exterior applications



HIGH TECH ROLL UP FAST ALUMINIUM DOOR | TECHNICAL SPECIFICATIONS

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- Patented rubber drive method

Door Type		Roll-up	
Use	Internal / External Door	Standard	
Door Sizes	Max Width	5500 mm	
	Max Height	5500 mm	
Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking	Opening Speed up to	
		Closing Speed	
Security Features	EN 13241-1	Standard	
Resistance to Wind Load	EN 12424	Class 3	
Door Leaf Material / Surface	Polyurethane filled RAL 9006 aluminium lamella	Standard	
Curtain	Aluminium 19.0 mm	Standard	
Guide Material / Surface	Aluminium Anodized	Standard	
	Painting in any RAL color	Optional	
Shaft / Operator Cover	Straight	Optional	
Operator and Control (German brand)	Connecting Voltage	1-phase	220V - 1 ph, N
		3-phase	380V - 3 ph, N
	Open-Stop-Close Button		Standard
	Protection Category (Operator / Control)		IP 54 / IP 65
	Emergency-OFF Button		Standard
	Closing Zone Monitoring	Light Grille IP 67	Standard
	External Route Monitoring	Photocell	Optional
	Door area Monitoring	Radar Presence Detector	Optional
		Induction Loop	Optional
	Electronic Limit Switch		Standard
Emergency Opening	Crank Handle	Standard	
	Chain	Optional	
Standard Curtain Colours	 White Similar to RAL 9016	 Brown Similar to RAL 8014	
	 Ivory Similar to RAL 1015	 Green Similar to RAL 6005	
	 Light beige	 Anthracite grey Similar to RAL 7016	